

1/1 - (C) FILE CAPLUS
 AN - 1986:212160 CAPLUS
 DN - 104:212160
 TI - Mortar composits
 IN - Nakayama, Fumio; Kawase, Hito; Toyama, Masao
 PA - Kikusui Kagaku Kogyo Co., Ltd., Japan
 SO - Jpn. Kokai Tokkyo Koho, 4 pp.

XP-002246340

CODEN: JKXXAF

DT - Patent

LA - Japanese

IC - ICM C04B028/06

ICS C04B007/32

ICI - C04B028-06, C04B014-06, C04B024-24

CC - 58-3 (Cement, Concrete, and Related Building Materials)

Section cross-reference(s): 38

FAN.CNT 1

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
------------	------	------	-----------------	------

PN - JP61040861	A	19860227	JP 1984-162514	19840731 <--
-----------------	---	----------	----------------	--------------

PR - JP 1984-162514			19840731	
---------------------	--	--	----------	--

AB - The mortar compns. consist of white cement (I), white aluminous cement (II) (II/I wt. ratio of 0.5-5), gypsum (III) (III/I wt. ratio of 0.3-2), polymer dispersion [(polymer component)/(I + II + III) wt. ratio of 0.1-1], colored sand (aggregates), and water. The mortar compns. prevent irregular color, significantly inhibit crack formation caused by mortar shrinkage, and are useful as a decorative floor surface of trains and ships, and as an internal or an external wall of buildings. Thus, I 25 was mixed with II 45, and III 35, then with a mixt. of poly(acrylic acid ester) dispersion [(polymer component)/(I + II + III) wt. ratio of 0.2], SiO₂ sand 200 parts, and water to give a mortar compn., and a galvanized sheet was coated with the compn. 4 mm thick (as dried) and cured. The resultant board was bent at an angle 120.degree. to show no crack formation. Several drops of water were dropped on the coating, and the coating did not show appreciable change 1 day later.

ST - shrinkage crack prevention; gypsum aluminous cement polymer mortar;

polyacrylate dispersion mortar compn; irregular color prevention colored sand

T - Mortar

(colored, contg. polymer dispersions for shrinkage crack prevention)

T - Sand

RL: USES (Uses)

(colored, in mortar, for even color)

T - Floors

(decorative, colored mortar for, contg. polymer dispersions for shrinkage crack prevention)

T - Polymers, uses and miscellaneous

RL: USES (Uses)

(dispersions, in mortar, for shrinkage crack prevention)

T - 79-10-7D, esters, polymers

RL: USES (Uses)

(dispersions, in mortar, for shrinkage crack prevention)

T - 13397-24-5, uses and miscellaneous

RL: USES (Uses)

(in mortar with polymer dispersions for shrinkage crack